



Model X40


Integrated Alarm & Control System



Model X40-8-N4X



Model X40-N7



Model X40-N1P

Description

Model X40 is a low power alarm and control system designed to monitor multiple gas detection sensors and/or a wide range of other field devices. The versatile control system is designed to receive and supervise inputs using either 4-20mA DC or Serial RS-485 Modbus™ and is available in two packages: Model X40-8 and Model X40-32. Both packages function as a Modbus™ Master and can be customized and expanded based on individual application needs using the stackable din-rail mounted I/O modules. All I/O modules are individually addressable and operate on 11.5-30VDC. The X40-8 provides power for up to eight field devices and can house up to six 4-channel I/O modules. The Model X40-32 provides power for up to 32 field devices and can house up to 12 4-channel I/O modules. The I/O modules available for use with the Model X40 include a 4-channel 4-20mA input module (DA-4), a 4-alarm relay output module (RL-4), a 4-channel 4-20mA output module (AO-4), and a 4-relay contact input module (DI-4). The modules can be mounted within the main system enclosure or installed remotely to simplify field wiring.

The Model X40 is completely field programmable using a small handheld magnet and offers advanced technology with intuitive, embedded intelligence. The control system displays real-time readings and field device status on a backlit LCD screen. During normal operation, the screen displays the alarm status and current reading (i.e., channel number, gas type, and gas concentration) for up to eight field devices simultaneously. The display is sequential and during normal operation it auto cycles through each of the active channel screens. Among the system's unique features is a wireless option that can be used with RXT-320 SmartWireless® transceivers. Enclosure options include: NEMA 4X, NEMA 1 panel mount, and NEMA 7.

Features

- 8 to 32 channel capacity
- Backlit LCD screen display
- Analog or RS-485 input options
- Easy intuitive field configuration
- Wire or distributed I/O
- Extensive event data logging
- SmartWireless® capable

Applications

- Oil and gas drilling rigs
- Oil and gas production sites
- Offshore production platforms
- Wastewater treatment plants
- Food and beverage processing
- Pulp and paper mills
- Refining and petrochemical



Model X40

Integrated Alarm & Control System

SYSTEM SPECIFICATIONS

System Capacity

Model X40-32-N1P: Up to 32 field devices
Model X40-8-N4X: Up to 8 field devices
Model X40-32-N4X: Up to 32 field devices
Model X40-32-N7: Up to 32 field devices
(analog or serial)

Indicators 1 1/8" by 5 3/4" backlit LCD

Alarm status LEDs

Display Accuracy

±1% of full scale value

Input Options

Analog 4-20 mA DC
RS-485 Modbus™ *(Only compatible with other Detcon products)
Relay Contacts

Output Options

4-20 mA DC
RS-485 Modbus™
Relay Contacts

Safety Approvals

CE Marking (Models X40-N4X & X40-SS)

Warranty

One Year

ENVIRONMENTAL SPECIFICATIONS

-4°F to + 158°F, -20°C to + 70°C

Storage Temperature Range

-40°F to + 185°F, -40°C to + 85°C

Operating Humidity Range

0-99% RH non-condensing

Specifications subject to change without notice

Order Guide

PN 95P-X32000-000	Model X40-32-N1P, General purpose panel mount hardware assembly 110/220 VAC, 24 VDC power supply (up to 32 active channels).
PN 954-X08000-000	Model X40-8-N4X, Wall mount ABS weatherproof enclosure 110/220 VAC, 24 VDC power supply (up to 8 active channels).
PN 954-X32000-000	Model X40-32-N4X, Wall mount ABS weatherproof enclosure 110/220 VAC, 24 VDC power supply (up to 32 active channels).
PN 957-X32000-000	Model X40-32-N7, Div 1 weatherproof enclosure 24 VDC power* for use in distributed I/O installations only (up to 32 active channels).

* 110/220 VAC, 24 VDC power supply optional. Addressable I/O modules sold separately.

MECHANICAL SPECIFICATIONS

Dimensions

Model X40-32-N1P: 10.5"W x 8"H x 12"D
Model X40-8-N4X: 12"W x 14"H x 7.75"D
Model X40-32-N4X: 16"W x 17.85"H x 9.5"D
Model X40-32-N7: 11"W x 9.15"H x 2.75"D

Weight

Model X40-32-N1P: 10 lbs
Model X40-8-N4X: 10 lbs
Model X40-32-N4X: 20 lbs
Model X40-32-N7: 10 lbs

ELECTRICAL OPTIONS

Power Input

115-230 VAC* or 11.5-30 VDC
* Option for Model X40-32-N7

Power Consumption

<0.25 Watt
(I/O module power consumption not included)
(Field device power consumption not included)

Electrical Classification

Model X40-32-N1P: NEMA 1 Panel Mount
Model X40-8-N4X: NEMA 4X Corrosion resistant weatherproof
Model X40-32-N4X: NEMA 4X Corrosion resistant weatherproof
Model X40-32-N7: NEMA 7 Class I; Division 1, Group C, D



AMERICAS
4055 Technology Forest Blvd.
The Woodlands,
TX 77381, USA
Tel.: +1-713-559-9200
Fax: +1-713-893-6729

EMEA
Zl Est, Rue Orfila,
CS 20417
62027 ARRAS CEDEX, France
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00

ASIA PACIFIC
290 Guiqiao Road
Pudong, Shanghai 201206
People's Republic of China
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365